



THIS IS GREENFIBER® RETROFIT ALL BORATE LOOSE FILL CELLULOSE INSULATION

Application Coverage Chart Dry install only. Do not add water.		25 lbs. (11.3 kg)		INS770LD	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Recubrimiento neto (Sin compensación para el entramado)		
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Cantidad máxima de pies cuadrados por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. (lbs/ft²) Peso mínimo por pie cuadrado (lb/pie2)
11	3.54	3.19	75.9	13.2	0.330
13	4.18	3.76	63.3	15.8	0.395
19	6.06	5.45	41.7	24.0	0.600
20	6.37	5.73	39.4	25.4	0.635
21	6.68	6.01	37.3	26.8	0.671
22	6.98	6.29	35.4	28.3	0.707
24	7.60	6.84	32.0	31.2	0.780
30	9.42	8.48	24.8	40.3	1.009
32	10.03	9.03	23.0	43.5	1.088
38	11.82	10.64	18.7	53.3	1.333
40	12.42	11.18	17.6	56.7	1.418
44	13.60	12.24	15.7	63.7	1.592
48	14.78	13.31	14.1	70.9	1.772
49	15.08	13.57	13.8	72.7	1.817
50	15.37	13.83	13.4	74.5	1.864
60	18.29	16.46	10.7	93.8	2.345

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25 LBS. USING A VOLUMATIC III, 3RD GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTING CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT 23.75 LBS.

Dry Dense Pack Sidewall Applications (3.5 pcf minimum installed density)		25 lbs. (11.3 kg)		INS770LD	
Wall Muro	Thermal Resistance Resistencia térmica (R)	Installed Thickness Espesor instalado (inch)	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado (lbs./ft²)	Maximum Square Feet per Bag Cantidad máxima de pies cuadrados por bolsa (16" oc) (24" oc)	
2 x 4	13	3.5	1.02	32.4	31.3
2 x 6	20	5.5	1.60	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDL 450A, WITH MATERIAL APPLIED DRY.

READ THIS BEFORE YOU BUY

What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:
800.228.0024 greenfiber.info@greenfiber.com

Corporate Office:
2500 Distribution Street, Suite 200, Charlotte NC 28203
(p) 800.228.0024 (f) 704.379.0685
www.greenfiber.com

Manufacturing Locations:
Albany, NY
Charlotte, NC
Delphos, OH
Norfolk, NE
Phoenix, AZ
Salt Lake City, UT
Tampa, FL
Waco, TX

