



THIS IS GREENFIBER® LOOSE FILL CELLULOSE INSULATION

Application Coverage Chart 23.25 lbs (10.6 kg) INS550LD-CAN  
 Dry install only – do not add water

RSI at 75° F Mean Temp. Valeur R à une température moyenne de 75 °F		Minimum Thickness — Épaisseur minimale				Minimum weight per Square Metre Poids Mini.		Maximum Sq. Metres Per Bag (no adjustment for framing) Maximum de metres carrés par sac (sans correction pour la charpente)	
		Initial Installed Thickness Épaisseur initiale de l'isolant installé		Settled Thickness Épaisseur après tassement					
RSI	R	mm	inches	mm	inches	kg/m <sup>2</sup>	lb/ft <sup>2</sup>	m <sup>2</sup>	ft <sup>2</sup>
10.5	60	458	18.0	409	16.1	9.8	2.0	1.1	11.5
8.8	50	385	15.1	343	13.5	8.3	1.7	1.3	13.8
7.7	44	336	13.2	300	11.8	7.2	1.5	1.5	15.7
7.0	40	306	12.0	273	10.7	6.6	1.3	1.6	17.3
6.7	38	292	11.5	261	10.3	6.3	1.3	1.7	18.1
6.3	36	275	10.8	246	9.7	5.9	1.2	1.8	19.2
6.1	35	266	10.5	238	9.4	5.7	1.2	1.8	19.9
5.9	34	258	10.1	230	9.1	5.5	1.1	1.9	20.5
5.6	32	244	9.6	218	8.6	5.2	1.1	2.0	21.6
5.3	30	231	9.1	207	8.1	5.0	1.0	2.1	22.9
4.9	28	214	8.4	191	7.5	4.6	0.9	2.3	24.7
4.2	24	183	7.2	164	6.4	3.9	0.8	2.7	28.9
3.5	20	153	6.0	136	5.4	3.3	0.7	3.2	34.6
2.8	16	122	4.8	109	4.3	2.6	0.5	4.0	43.3
2.6	15	114	4.5	101	4.0	2.4	0.5	4.3	46.6
2.4	14	105	4.1	94	3.7	2.2	0.5	4.7	50.5
2.1	12	92	3.6	82	3.2	2.0	0.4	5.4	57.7
1.7	10	74	2.9	66	2.6	1.6	0.3	6.6	71.3
1.4	8	61	2.4	55	2.1	1.3	0.3	8.0	86.6

Sidewall Application/ Application Dans Les Murs								Maximum Sq. Metres Per Bag Maximum de metres cares par sac	
								38 x 140 @ 406 mm o.c.	2 x 6 @ 16 in. o.c.
2.3	13	89	3.5	—	—	4.45	0.91	2.6	28
3.6	20	140	5.5	—	—	6.99	1.43	1.7	18

THE ABOVE COVERAGE FIGURES COMPENSATE FOR SETTLING AND ARE FOR ESTIMATING PURPOSES ONLY. TO ACHIEVE STATED R-VALUE DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. ACTUAL COVERAGE WILL BE INFLUENCED BY JOB CONDITIONS AND BARRIER REQUIREMENTS. WHEN INSTALLING, ADD 12% TO MINIMUM SETTLED THICKNESS FOR HORIZONTAL BLOWN APPLICATION. DO NOT ADD WATER TO THIS PRODUCT.  
 THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT 23.25 LBS./10.5 KG.. DO NOT ADD WATER TO THIS PRODUCT.  
 DANS LES CHIFFRES INIQUÉS AU TABLEAU DE RECOUVREMENT, ON A TENU COMPTE DU FACTEUR DE TASSEMENT; CES CHIFFRES NE DOIVENT SERVIR QU'À ESTIMER LES QUANTITÉS REQUISES. POUR ATTEINDRE LE FACTEUR "RSI" OU LE FACTEUR "R" DESIRÉ, VOUS NE DEVEZ PAS DÉPASSER LE NOMBRE DE METRES CARRÉS MAXIMUM PAR SAC, CEPENDANT, LES CONDITIONS D'APPLICATION AINSI QUE LES BESOINS D'ÉTANCHEÏTE POURRONT CAUSER DES VARIATIONS DANS LES QUANTITÉS NÉCESSAIRES. AU MOMENT DE L'INSTALLATION, VOUS DEVEZ AJOUTER 12% À L'ÉPAISSEUR MINIMUM APRÈS TASSEMENT DE L'ISOLANT SOUFFLÉ SUR UNE SURFACE HORIZONTALE. N'AJOUTEZ PAS D'EAU À CE PRODUIT.  
 Le niveau de couverture ci-dessus est basé sur un poids nominal de sac de 23.25 livres/10.5 kg.. N'ajoutez pas d'eau à ce produit.

**READ THIS BEFORE YOU BUY**

**What you should know about R-values**

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:  
**800.228.0024 greenfiber.info@greenfiber.com**

Corporate Office:  
 2500 Distribution Street, Suite 200, Charlotte NC 28203  
 (p) 800.228.0024 (f) 704.379.0685  
 www.greenfiber.com

Manufacturing Locations:  
 Albany, NY                      Phoenix, AZ  
 Charlotte, NC                  Salt Lake City, UT  
 Delphos, OH                    Tampa, FL  
 Norfolk, NE                      Waco, TX

