



THIS IS GREENFIBER® ALL BORATE STABILIZED CELLULOSE INSULATION

Application Coverage Chart		30 lbs (13.6 kg)				INS745	
R-Value at 75° F Mean Temp. Valor de resistencia termica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Exesor minimo (en pulgadas)		Net Coverage (no adjustment for framing) Recubrimiento neto (Sin compensacion para el entramado)			Gross Coverage (based on 2" x 6" framing on 16" centers) Recubrimiento Bruto (Bosado en armazón de 5.08 cm x 15.24 cm (2" x 6" en centro de 40.64 cm (16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad minima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. (lbs/ft²) Peso minimo por pie cuadrado (lb/pie²)	Maximum Sq. Ft. per Bag Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad minima de bolsas por 1,000 pies cuadrados
R11	3.26	3.03	102.0	9.8	0.294	112.5	8.9
R13	3.87	3.60	84.4	11.9	0.356	93.1	10.7
R19	5.68	5.28	54.6	18.3	0.549	60.1	16.6
R22	6.56	6.10	46.1	21.7	0.651	50.0	20.0
R26	7.73	7.19	37.9	26.4	0.791	40.6	24.6
R30	8.89	8.27	32.0	31.3	0.938	33.9	29.5
R32	9.47	8.81	29.6	33.8	1.01	31.3	31.9
R38	11.18	10.40	24.0	41.6	1.25	25.2	39.7
R40	11.75	10.93	22.5	44.4	1.33	23.6	42.4
R44	12.88	11.97	20.0	49.9	1.50	20.9	47.9
R48	14.00	13.02	18.0	55.7	1.67	18.6	53.7
R49	14.28	13.28	17.5	57.2	1.72	18.1	55.1
R50	14.56	13.54	17.0	58.7	1.76	17.7	56.6
R60	17.33	16.12	13.5	74.2	2.23	13.9	72.0

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 16% AND 25% IN ATTIC APPLICATIONS. THIS PRODUCT IS NOT FOR DRY LOOSE-FILL ATTIC/FLOOR APPLICATIONS. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 28.5 LBS.

READ THIS BEFORE YOU BUY

What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:

GreenFiber Corporate Office
2500 Distribution Street, Suite 200
Charlotte, NC 28203

(p) 800.228.0024 (f) 704.379.0685
(e) greenfiber.info@greenfiber.com
www.greenfiber.com

MANUFACTURING LOCATIONS:

Albany, NY
Charlotte, NC
Delphos, OH
Norfolk, NE
Phoenix, AZ
Salt Lake City, UT
Tampa, FL
Waco, TX

