



ATTIC CARD

THIS IS GREENFIBER® BLOW-IN NATURAL FIBER CELLULOSE INSULATION

Application Coverage Chart			19.05 lbs (8.64 kg)			(INS541LD)	
R-Value at 75° F Mean Temp.  Valor de resistencia termica (valor R) a 75 F de temperatura media	Minimum Thickness (inches)  Espesor minimo (en pulgadas)		Net Coverage (no adjustment for framing)  Recubrimiento neto (Sin compensacion para el entramado)			Gross Coverage (based on 2" x 6" framing on 16" centers)  Recubrimiento Bruto (Bosado en armazón de 5.08 cm x 15.24 cm (2" x 6" en centro de 40.64 cm (16"))	
	Initial Installed Thickness  Espesor inicial instalado	Settled Thickness  Espesor asentado	Maximum Sq. Ft. per Bag  Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft.  Cantidad minima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. (lbs/ft <sup>2</sup> )  Peso minimo por pie cuadrado (lb/pie <sup>2</sup> )	Maximum Sq. Ft. per Bag  Metros Cuadrado máximos por bolsa	Minimum Bags per 1,000 Sq. Ft.  Cantidad minima de bolsas por 100 metros cuadrados
R 13	4.29	3.86	56.0	17.9	0.340	61.8	16.2
R 19	6.19	5.57	36.7	27.2	0.519	40.0	25.0
R 22	7.12	6.41	31.1	32.2	0.613	33.5	29.8
R 25	8.05	7.25	26.8	37.2	0.710	28.7	34.9
R 30	9.57	8.62	21.7	46.1	0.878	22.9	43.6
R 38	11.97	10.77	16.4	61.1	1.164	17.1	58.5
R 49	15.20	13.68	12.0	83.5	1.591	12.4	80.7
R 60	18.37	16.53	9.3	108.1	2.059	9.5	105.0

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 19.05 LBS USING THE GREENFIBER MONARCH BLOWING MACHINE. SETTINGS ARE NOT ADJUSTABLE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT MUST BE INSTALLED DRY. THIS COVERAGE CHART DOES NOT APPLY TO FLOOR APPLICATIONS. DO NOT ADD WATER TO THIS PRODUCT. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 18.1 LBS.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ bags of this insulation to cover \_\_\_\_\_ square feet of area.

Builder's Signature: \_\_\_\_\_  
 Company Name: \_\_\_\_\_  
 Date: \_\_\_\_\_

Applicator's Signature: \_\_\_\_\_  
 Company Name: \_\_\_\_\_  
 Date: \_\_\_\_\_

FOR MORE INFORMATION CONTACT GREENFIBER:

**800.228.0024**  
**GreenFiber.info@greenfiber.com**

GreenFiber Corporate Office  
 2500 Distribution Street, Suite 200  
 Charlotte NC 28203  
 (p) 800.228.0024 (f) 704.379.0685  
[www.greenfiber.com](http://www.greenfiber.com)

MANUFACTURING LOCATIONS:

- Albany, NY
- Charlotte, NC
- Delphos, OH
- Norfolk, NE
- Phoenix, AZ
- Salt Lake City, UT
- Tampa, FL
- Waco, TX

