



ATTIC CARD

THIS IS GREENFIBER® STABILIZED FORMULA INSULATION

Application Coverage Chart		30 lbs (13.6 kg)						INS500-CAN	
Thermal Resistance Resistencia térmica		Minimum Applied Thickness Épaisseur minimale appliquée		Minimum Design (Settled) Thickness Épaisseur minimale théorique (après tassement)		Minimum Mass per Unit Area Masse minimale par unité de surface		Maximum Coverage Per Bag (no adjustment for framing) Couverture maximale par sac (sans correction selon la charpente)	
RSI	R	mm	inch	mm	inch	kg/m <sup>2</sup>	lb/ft <sup>2</sup>	m <sup>2</sup> /Bag	ft <sup>2</sup> /Bag
m <sup>2</sup> /KW	h ft <sup>2</sup> F/Btu								
1.4	8	59.5	2.34	55.3	2.18	1.22	0.250	11.1	119.8
1.7	10	72.2	2.84	67.2	2.64	1.48	0.304	9.2	98.6
2.1	12	89.2	3.51	83.0	3.27	1.83	0.376	7.4	79.9
2.4	14	102	4.01	94.8	3.73	2.10	0.429	6.5	69.9
2.6	15	110	4.35	103	4.04	2.27	0.465	6.0	64.5
2.8	16	119	4.68	111	4.36	2.45	0.501	5.6	59.9
3.5	20	149	5.85	138	5.44	3.06	0.626	4.5	47.9
4.2	24	178	7.03	166	6.53	3.67	0.751	3.7	39.9
4.9	28	208	8.20	194	7.62	4.28	0.877	3.2	34.2
5.3	30	225	8.87	209	8.24	4.63	0.95	2.9	31.6
5.6	32	238	9.37	221	8.71	4.89	1.00	2.8	29.9
5.9	34	251	9.87	233	9.18	5.15	1.06	2.6	28.4
6.1	35	259	10.20	241	9.49	5.33	1.09	2.6	27.5
6.3	36	268	10.54	249	9.80	5.50	1.13	2.5	26.6
7.0	40	297	11.71	277	10.9	6.11	1.25	2.2	24.0
7.7	44	327	12.88	304	12.0	6.73	1.38	2.0	21.8
8.8	50	374	14.74	348	13.7	7.70	1.58	1.8	19.0
10.6	60	450	17.73	419	16.5	9.26	1.90	1.5	15.8
12.3	70	523	20.57	486	19.1	10.74	2.20	1.3	13.6
14.1	80	599	23.59	557	21.9	12.32	2.52	1.1	11.9

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS PER CANADIAN STANDARD S703-09. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER UNIT AREA AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 28.5 LBS.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ bags of this insulation to cover \_\_\_\_\_ square feet of area.

Builder's Signature: \_\_\_\_\_  
 Company Name: \_\_\_\_\_  
 Date: \_\_\_\_\_

Applicator's Signature: \_\_\_\_\_  
 Company Name: \_\_\_\_\_  
 Date: \_\_\_\_\_

FOR MORE INFORMATION CONTACT GREENFIBER:

**800.228.0024**  
**GreenFiber.info@greenfiber.com**

GreenFiber Corporate Office  
 2500 Distribution Street, Suite 200  
 Charlotte NC 28203, USA  
[www.greenfiber.com](http://www.greenfiber.com)

MANUFACTURING LOCATIONS:

- Albany, NY
- Charlotte, NC
- Delphos, OH
- Norfolk, NE
- Phoenix, AZ
- Salt Lake City, UT
- Tampa, FL
- Waco, TX

