



ATTIC CARD

THIS IS GREENFIBER (STABILIZED FOR ATTICS ONLY CELLULOSE INSULATION

Application Coverage Chart		30 lbs (13.6 kg)		INS500	
R-Value at 75° F Mean T emp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Recubrimiento neto (Sin compensación para el entramado)		
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Cantidad máxima de pies cuadrados por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. (lbs/ft ²) Peso mínimo por pie cuadrado (lb/pie ²)
11	3.30	3.07	105.2	9.5	0.285
13	3.92	3.64	87.2	11.5	0.344
19	5.74	5.34	56.7	17.6	0.529
22	6.64	6.18	47.9	20.9	0.626
28	8.42	7.83	36.2	27.6	0.828
30	9.00	8.37	33.4	29.9	0.898
32	9.58	8.91	30.9	32.3	0.969
38	11.32	10.53	25.2	39.7	1.19
40	11.89	11.06	23.7	42.2	1.27
44	13.03	12.12	21.1	47.4	1.42
48	14.17	13.17	18.9	52.8	1.58
49	14.45	13.44	18.5	54.2	1.63
50	14.73	13.70	18.0	55.6	1.67
60	17.53	16.30	14.3	70.0	2.10

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS. USING A VOLUMATIC III, 3RD GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1,000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 16% AND 25% IN ATTIC APPLICATIONS. THIS COVERAGE CHART DOES NOT APPLY TO DRY LOOSE-FILL ATTIC/FLOOR APPLICATIONS. THIS PRODUCT IS NOT INTENDED FOR SPRAY APPLIED OR DRY DENSE-PACK WALL APPLICATIONS. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 28.5 LBS.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the coverage chart recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____
 Company Name: _____
 Date: _____

Applicator's Signature: _____
 Company Name: _____
 Date: _____

FOR MORE INFORMATION CONTACT GREENFIBER:

800.228.0024
greenfiber.info@greenfiber.com

GreenFiber Corporate Office
 5500 77 Center Drive, Suite 100
 Charlotte NC 28217
www.greenfiber.com

MANUFACTURING LOCATIONS:

- Delphos, OH 45833
- Debert, Nova Scotia
- Norfolk, NE 68701
- Chandler, AZ 85043
- Salt Lake City, UT 84119
- Tampa, FL 33605
- Vars, Ontario
- Waco, TX 76704
- Wilkes-Barre, PA 18702



UL Classified.
 see complete marking on back of packaging

