



# CEL-PAK

ATTIC CARD

## THIS IS GREENFIBER® RETROFIT ALL BORATE LOOSE FILL CELLULOSE INSULATION

Net Coverage - Attics		25.0 lb. - settled density 1.40 lbs./cu. ft.			
R-Value @ 75° F	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Bags per 1,000 sq. ft. No Joists	Net Coverage sq. ft./Bag No Joists	Minimum Weight lb/sq. ft.
13	4.3	3.8	11.7	85.8	0.29
19	5.9	5.3	19.8	50.5	0.50
22	6.8	6.1	24.0	41.6	0.60
30	9.1	8.1	35.4	28.3	0.88
38	11.4	10.2	46.8	21.4	1.17
49	14.5	13.1	62.6	16.0	1.56
60	17.7	16.0	78.4	12.8	1.96

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. ACTUAL COVERAGE MAY VARY BASED ON CONDITIONS AND IS NOT GUARANTEED BY THE MANUFACTURER. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE ACHIEVEMENT OF THE SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 23.75 LBS.

Net Coverage - Sidewalls		25.0 lb. bag - blown in at 3.1 lbs./cu. ft.			
R-Value @ 75° F	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Bags per 1,000 sq. ft. No Joists	Net Coverage sq. ft./Bag No Joists	Minimum Weight lb/sq. ft.
13	2x4	3.5	36.2	27.6	.905
20	2x6	5.5	56.8	17.6	1.420

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDL 450A, WITH MATERIAL APPLIED DRY.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

### CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ bags of this insulation to cover \_\_\_\_\_ square feet of area.

Builder's Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Date: \_\_\_\_\_

Applicator's Signature: \_\_\_\_\_

Company Name: \_\_\_\_\_

Date: \_\_\_\_\_

### FOR MORE INFORMATION CONTACT GREENFIBER:

**800.228.0024**

**[greenfiber.info@greenfiber.com](mailto:greenfiber.info@greenfiber.com)**

GreenFiber Corporate Office  
5500 77 Center Drive, Suite 100  
Charlotte NC 28217  
(p) 800.228.0024 (f) 704.379.0685

[www.greenfiber.com](http://www.greenfiber.com)

### MANUFACTURING LOCATIONS:

- Delphos, OH
- Debert, Nova Scotia
- Norfolk, NE
- Chandler, AZ
- Salt Lake City, UT
- Tampa, FL
- Vars, Ontario
- Waco, TX
- Wilkes-Barre, PA

