



THIS IS GREENFIBER® RETROFIT ALL BORATE LOOSE FILL CELLULOSE INSULATION

| Net Coverage - Attics | | | 25.0 lb. - settled density 1.40 lbs./cu. ft. | | |
|-----------------------|-----------------------------------|---------------------------------|--|------------------------------------|---------------------------|
| R-Value @ 75° F | Initial Installed Thickness (in.) | Minimum Settled Thickness (in.) | Bags per 1,000 sq. ft. No Joists | Net Coverage sq. ft./Bag No Joists | Minimum Weight lb/sq. ft. |
| 13 | 4.3 | 3.8 | 11.7 | 85.8 | 0.29 |
| 19 | 5.9 | 5.3 | 19.8 | 50.5 | 0.50 |
| 22 | 6.8 | 6.1 | 24.0 | 41.6 | 0.60 |
| 30 | 9.1 | 8.1 | 35.4 | 28.3 | 0.88 |
| 38 | 11.4 | 10.2 | 46.8 | 21.4 | 1.17 |
| 49 | 14.5 | 13.1 | 62.6 | 16.0 | 1.56 |
| 60 | 17.7 | 16.0 | 78.4 | 12.8 | 1.96 |

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. ACTUAL COVERAGE MAY VARY BASED ON CONDITIONS AND IS NOT GUARANTEED BY THE MANUFACTURER. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE ACHIEVEMENT OF THE SPECIFIED R-VALUE. THIS PRODUCT IS INTENDED FOR DRY APPLICATION ONLY. DO NOT ADD WATER TO THIS PRODUCT. MINIMUM NET WEIGHT IS 23.75 LBS.

| Net Coverage - Sidewalls | | | 25.0 lb. bag - blown in at 3.1 lbs./cu. ft. | | |
|--------------------------|-----------------------------------|---------------------------------|---|------------------------------------|---------------------------|
| R-Value @ 75° F | Initial Installed Thickness (in.) | Minimum Settled Thickness (in.) | Bags per 1,000 sq. ft. No Joists | Net Coverage sq. ft./Bag No Joists | Minimum Weight lb/sq. ft. |
| 13 | 2x4 | 3.5 | 36.2 | 27.6 | .905 |
| 20 | 2x6 | 5.5 | 56.8 | 17.6 | 1.420 |

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDL 450A, WITH MATERIAL APPLIED DRY.

READ THIS BEFORE YOU BUY

What you should know about R-values

This chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy. There are other factors to consider. The amount of the insulation you need depends on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel. To get the marked R-value, it is essential that this insulation be installed properly.

FOR MORE INFORMATION CONTACT GREENFIBER:

GreenFiber Corporate Office
2500 Distribution Street, Suite 200
Charlotte, NC 28203

(p) 800.228.0024 (f) 704.379.0685
(e) greenfiber.info@greenfiber.com
www.greenfiber.com

MANUFACTURING LOCATIONS:

Delphos, OH 45833
Debert, Nova Scotia
Norfolk, NE 68701
Chandler, AZ 85043
Salt Lake City, UT 84119
Tampa, FL 33605
Vars, Ontario
Waco, TX 76704
Wilkes-Barre, PA 18702

