

## ATTIC COVERAGE CHART – LOOSE-FILL AND STABILIZED APPLICATIONS

Tabla de Cobertura de Ático - Aplicaciones de Relleno Suelto y Aplicaciones Estabilizadas

R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) at 75 F de temperatura media	25lbs (11.3kg)			SANCTUARY®					
	Minimum Thickness (inches) Espesor mínimo (en pulgadas)			Net Coverage (no adjustment for framing) Cobertura neta (sin compensación para la estructura)			Net Coverage (adjusted for 2" x 6" framing on 16" centers) Cobertura neta (con compensación para una estructura de 2" x 6" en centros de 16")		
	STABILIZED Initial Installed Thickness Espesor inicial instalado	LOOSE-FILL Initial Installed Thickness Espesor asentado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	
13	3.8	3.9	3.6	65.8	15.2	0.38	72.6	13.8	
19	5.5	5.7	5.3	44.2	22.6	0.57	48.8	20.5	
22	6.4	6.6	6.1	38.0	26.3	0.66	41.2	24.2	
30	8.7	8.9	8.3	25.9	38.6	0.97	27.4	36.5	
38	10.9	11.2	10.4	19.0	52.6	1.32	19.9	50.1	
44	12.6	12.9	12.0	15.7	63.5	1.59	16.5	60.8	
49	13.9	14.3	13.3	14.1	70.8	1.80	14.6	68.5	
60	16.9	17.3	16.1	11.6	86.0	2.20	12.0	83.5	

### LOOSE-FILL APPLICATIONS

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25 LBS USING A VOLUMATIC III, 3RD GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO ENSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 23.75 LBS. IN ACCORDANCE WITH ASTM C-739.

### STABILIZED APPLICATIONS

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 25.0 LBS USING A VOLUMATIC III, 3RD GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO ENSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE APPLICATION OF SPECIFIED R-VALUE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 16% AND 22% IN ATTIC APPLICATIONS. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. MINIMUM NET WEIGHT IS 23.75 LBS. IN ACCORDANCE WITH ASTM C-1497. THE STABILIZED APPLICATION IS FOR PROFESSIONAL INSTALLERS ONLY USING SPECIALIZED EQUIPMENT.

## SIDEWALL & FLOOR COVERAGE CHART

### DENSE-PACK APPLICATION

Tabla de Cobertura de Piso y Pared Lateral -Aplicaciones de Paquete Denso

Framing Estructura	Thermal Resistance (R value) Resistencia térmica (R)	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt Per Square foot lb/ft² Peso mínimo por pie cuadrado lb/ft²	Maximum Coverage per Bag (Adjusted for Framing) Cobertura máxima por bolsa (con compensación para la estructura)	
				16 inch o.c. ft²/Bag 16 pulgadas o.c. pie²/bolsa	24 inch o.c. ft²/Bag 24 pulgadas o.c. pie²/bolsa
				Dry Dense-Pack Sidewall & Floor Applications (3.5 pcf minimum installed density) SANCTUARY®	
2 x 4	13	3.5	1.02	27.0	26.1
2 x 6	21	5.5	1.60	17.2	16.6
2 x 8	28	7.5	2.19	12.6	12.1

This coverage chart is for dry applications only and is based on the Krendl KS200, with material applied dry.

## SIDEWALL COVERAGE CHART

### SPRAY APPLIED APPLICATIONS

Tabla de Cobertura de Pared Lateral - Aplicaciones Aplicadas por Spray

Framing Estructura	Thermal Resistance (R value) Resistencia térmica (R)	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt Per Square foot lb/ft² Peso mínimo por pie cuadrado lb/ft²	Maximum Coverage per Bag (Adjusted for Framing) Cobertura máxima por bolsa (con compensación para la estructura)	
				16 inch o.c. ft²/Bag 16 pulgadas o.c. pie²/bolsa	24 inch o.c. ft²/Bag 24 pulgadas o.c. pie²/bolsa
				Spray-Applied Sidewall Applications (2.75 pcf minimum installed density) SANCTUARY®	
2 x 4	13	3.5	0.79	35.0	33.8
2 x 6	21	5.5	1.24	22.3	21.6

This coverage chart is based on the Volumatic III, 2nd gear, 6" gate. The installed moisture content must be between 25% and 35% as measured by a hand held moisture meter. Do not cover the insulation until the insulation moisture content, measured and documented after a minimum period of 24 hrs from the time of installation, reaches 25% or less in accordance with Greenfiber's Wallspray Manual. Install dry dense pack Sanctuary insulation in all exterior wall sections where added vapor impediments, such as cabinets, mirrors, tubs, and shower enclosures are located. If unsure where impediments are located, dry dense pack the entire exterior wall section(s). Non-standard or unusual wall configurations (i.e., other than 2x4 and 2x6 walls) can affect thermal and sound properties and require special installation considerations. These types of designs should be analyzed and, if necessary, tested prior to plan review. Contact Greenfiber technical representative for applications or framing that is not included on these charts.

Greenfiber® provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, Greenfiber® Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

This insulation has been installed in conformance with the above recommendations, to provide a value of R-\_\_\_\_\_ using \_\_\_\_\_ bags of this insulation to cover \_\_\_\_\_ square feet of area at an installed thickness of \_\_\_\_\_ (in).

Builder's Signature

Company Name

Date

Applicator's Signature

Company Name

Date

Manufactured by  
**Greenfiber®**

Toll-Free 800-228-0024  
www.greenfiber.com

Greenfiber® is a registered trademark of Greenfiber®  
© 2023 Greenfiber®.

All rights reserved.

Greenfiber®  
5500 77 Center Drive,  
Suite 100 Charlotte, NC 28217

Made in USA

PM-6.3328 Rev F 11/23

Decatur, AL 35601  
Tampa, FL 33605  
Eastanollee, GA 30538  
Hickory, KY 42051  
Webberville, MI 48892  
Lester Prairie, MN 55354  
Norfolk, NE 68701  
Chambersburg, PA 17201  
Wilkes Barre, PA 18702  
Waco, TX 76704  
Salt Lake City, UT 84119  
Debert, Nova Scotia  
Chandler, AZ 85225

